

SEP 17 2007

Application No.: 09/485559
Docket No.: FL1049USPCT

Page 2

Amendments to Claims

Claim 1-12 (Canceled)

Claim 13 (Amended) A process for separating difluoromethane (HFC-32) from a first mixture ~~comprising~~ consisting essentially of difluoromethane (HFC-32) and dichlorodifluoromethane (CFC-12), comprising the steps of:

contacting the first mixture with a hydrocarbon extractive agent having from 5 to 9 carbon atoms and having a normal boiling point greater than about 30°C and less than about 155°C to form a second mixture;

separating difluoromethane (HFC-32) from dichlorodifluoromethane (CFC-12) by distilling the second mixture in an extractive distillation zone; and

recovering difluoromethane (HFC-32) substantially free of dichlorodifluoromethane (CFC-12) as an overhead product, and recovering said extractive agent and dichlorodifluoromethane (CFC-12) from the bottom of said extractive distillation zone.

Claim 14 (Previously presented) The process of Claim 13 wherein the hydrocarbon extractive agent is selected from the group consisting of n-pentane, 2-methylpentane, 3-methylpentane, cyclopentane, methylcyclopentane, n-hexane, cyclohexane and n-heptane.

Claim 15 (Previously presented) The process of Claim 13 wherein the difluoromethane (HFC-32) recovered from the second mixture contains less than about 50 ppmw dichlorodifluoromethane (CFC-12).

Claim 16 (Previously presented) The process of Claim 13 wherein the difluoromethane (HFC-32) recovered from the second mixture contains less than about 0.1 ppmw dichlorodifluoromethane (CFC-12).

Claim 17 (Currently amended) A process for separating difluoromethane (HFC-32) from a first mixture ~~comprising~~ consisting essentially of difluoromethane (HFC-32) and dichlorodifluoromethane (CFC-12), comprising the steps of:

contacting the first mixture with an extractive agent selected from the group consisting of:

oxygen-containing extractive agents consisting of alcohols having a normal boiling point greater than about 60°C and less than about 100°C and represented by the formula $C_xH_{2x+1}OH$, wherein x is from 1 to 3, and ketones having a normal boiling point greater than about 50°C and less than about 110°C

Application No.: 09/485559
Docket No.: FL1049USPCT

Page 3

and represented by the formula $C_yH_{2y+1}COC_zH_{2z+1}$, wherein y and z are 1 or greater and y+z is at most 5, and

chlorocarbon extractive agents consisting of chlorocarbons having a normal boiling point greater than about 39°C and less than about 150°C and represented by the formula $C_sH_{2s+2}Cl_t$, wherein s is 1 or 2 and t is from 2 to 4 to form a second mixture;

separating difluoromethane (HFC-32) from dichlorodifluoromethane (CFC-12) by distilling the second mixture in an extractive distillation zone; and
recovering difluoromethane (HFC-32) substantially free of dichlorodifluoromethane (CFC-12), together with said extractive agent from the bottom of said extractive distillation zone.

Claim 18 (Previously presented) The process of Claim 17 wherein the oxygen-containing extractive agent is selected from the group consisting of methanol, ethanol, propanol, isopropanol, propanone, and butanone.

Claim 19 (Previously presented) The process of Claim 17 wherein the chlorocarbon extractive agent is methylene chloride.

Claim 20 (Previously presented) The process of Claim 17 wherein the difluoromethane (HFC-32) recovered from the second mixture contains less than about 50 ppmw dichlorodifluoromethane (CFC-12).

Claim 21 (Previously presented) The process of Claim 17 wherein the difluoromethane (HFC-32) recovered from the second mixture contains less than about 0.1 ppmw dichlorodifluoromethane (CFC-12).

Claim 22 (Currently Amended) A process for separating difluoromethane (HFC-32) from a first mixture ~~comprising~~ consisting essentially of difluoromethane (HFC-32) and 1,1,1-trifluoroethane (HFC-143a), comprising the steps of:

contacting the first mixture with a hydrocarbon extractive agent having from 5 to 9 carbon atoms and having a normal boiling point greater than about 30°C and less than about 155°C to form a second mixture;

separating difluoromethane (HFC-32) from 1,1,1-trifluoroethane (HFC-143a) by distilling the second mixture in an extractive distillation zone; and

recovering difluoromethane (HFC-32) substantially free of 1,1,1-trifluoroethane (HFC-143a) as an overhead product, and recovering said extractive agent and 1,1,1-trifluoroethane (HFC-143a) from the bottom of said extractive distillation zone.

Application No.: 09/485559
Docket No.: FL1049USPCT

Page 4

Claim 23 (Previously presented) The process of Claim 22 wherein the hydrocarbon extractive agent is selected from the group consisting of n-pentane, 2-methylpentane, 3-methylpentane, cyclopentane, methylcyclopentane, n-hexane, cyclohexane and n-heptane.

Claim 24 (Previously presented) The process of Claim 22 wherein the difluoromethane (HFC-32) recovered from the second mixture contains less than about 50 ppmw 1,1,1-trifluoroethane (HFC-143a).

Claim 25 (Previously presented) The process of Claim 22 wherein the difluoromethane (HFC-32) recovered from the second mixture contains less than about 0.1 ppmw 1,1,1-trifluoroethane (HFC-143a).

Claim 26 (Currently amended) A process for separating difluoromethane (HFC-32) from a first mixture ~~comprising~~ consisting essentially of difluoromethane (HFC-32) and 1,1,1-trifluoroethane (HFC-143a), comprising the steps of:

contacting the first mixture with an extractive agent selected from the group consisting of:

ketones having a normal boiling point greater than about 50°C and less than about 110°C and represented by the formula $C_yH_{2y+1}COC_zH_{2z+1}$, wherein y and z are 1 or greater and y+z is at most 5, and

chlorocarbon extractive agents consisting of chlorocarbons having a normal boiling point greater than about 39°C and less than about 150°C and represented by the formula $C_sH_{2s+2-t}Cl_t$, wherein s is 1 or 2 and t is from 2 to 4 to form a second mixture;

separating difluoromethane (HFC-32) from 1,1,1-trifluoroethane (HFC-143a) by distilling the second mixture in an extractive distillation zone; and

recovering difluoromethane (HFC-32) substantially free of 1,1,1-trifluoroethane (HFC-143a), together with said extractive agent from the bottom of said extractive distillation zone.

Claim 27 (Previously presented) The process of Claim 26 wherein the ketone extractive agent is selected from the group consisting of propanone and butanone.

Claim 28 (Previously presented) The process of Claim 26 wherein the chlorocarbon extractive agent is methylene chloride.

Application No.: 09/485559
Docket No.: FL1049USPCT

Page 5

Claim 29 (Previously presented) The process of Claim 26 wherein the difluoromethane (HFC-32) recovered from the second mixture contains less than about 50 ppmw 1,1,1-trifluoroethane (HFC-143a).

Claim 30 (Previously presented) The process of Claim 26 wherein the difluoromethane (HFC-32) recovered from the second mixture contains less than about 0.1 ppmw 1,1,1-trifluoroethane (HFC-143a).

Claim 31 (Currently amended) A process for separating difluoromethane (HFC-32) from a first mixture ~~comprising~~ consisting essentially of difluoromethane (HFC-32) and chloropentafluoroethane (CFC-115), comprising the steps of:

contacting the first mixture with a hydrocarbon extractive agent having from 5 to 9 carbon atoms and having a normal boiling point greater than about 30°C and less than about 155°C to form a second mixture;

separating difluoromethane (HFC-32) from chloropentafluoroethane (CFC-115) by distilling the second mixture in an extractive distillation zone; and

recovering difluoromethane (HFC-32) substantially free of chloropentafluoroethane (CFC-115) as an overhead product, and recovering said extractive agent and chloropentafluoroethane (CFC-115) from the bottom of said extractive distillation zone.

Claim 32 (Previously presented) The process of Claim 31 wherein the hydrocarbon extractive agent is selected from the group consisting of n-pentane, 2-methylpentane, 3-methylpentane, cyclopentane, methylcyclopentane, n-hexane, cyclohexane and n-heptane.

Claim 33 (Previously presented) The process of Claim 31 wherein the difluoromethane (HFC-32) recovered from the second mixture contains less than about 50 ppmw chloropentafluoroethane (CFC-115).

Claim 34 (Previously presented) The process of Claim 31 wherein the difluoromethane (HFC-32) recovered from the second mixture contains less than about 0.1 ppmw chloropentafluoroethane (CFC-115).

Claim 35 (Currently amended) A process for separating difluoromethane (HFC-32) from a first mixture ~~comprising~~ consisting essentially of difluoromethane (HFC-32) and chloropentafluoroethane (CFC-115), comprising the steps of:

contacting the first mixture with an extractive agent selected from the group consisting of:

Application No.: 09/485559
Docket No.: FL1049USPCT

Page 6

oxygen-containing extractive agents consisting of alcohols having a normal boiling point greater than about 60°C and less than about 100°C and represented by the formula $C_xH_{2x+1}OH$, wherein x is from 1 to 3, and ketones having a normal boiling point greater than about 50°C and less than about 110°C and represented by the formula $C_yH_{2y+1}COC_zH_{2z+1}$, wherein y and z are 1 or greater and y+z is at most 5, and

chlorocarbon extractive agents consisting of chlorocarbons having a normal boiling point greater than about 39°C and less than about 150°C and represented by the formula $C_sH_{2s+2-t}Cl_t$, wherein s is 1 or 2 and t is from 2 to 4 to form a second mixture;

separating difluoromethane (HFC-32) from chloropentafluoroethane (CFC-115) by distilling the second mixture in an extractive distillation zone; and
recovering difluoromethane (HFC-32) substantially free of chloropentafluoroethane (CFC-115), together with said extractive agent from the bottom of said extractive distillation zone.

Claim 36 (Previously presented) The process of Claim 35 wherein the oxygen-containing extractive agent is selected from the group consisting of methanol, ethanol, propanol, isopropanol, propanone, and butanone.

Claim 37 (Previously presented) The process of Claim 35 wherein the chlorocarbon extractive agent is methylene chloride.

Claim 38 (Previously presented) The process of Claim 35 wherein the difluoromethane (HFC-32) recovered from the second mixture contains less than about 50 ppmw chloropentafluoroethane (CFC-115).

Claim 39 (Previously presented) The process of Claim 35 wherein the difluoromethane (HFC-32) recovered from the second mixture contains less than about 0.1 ppmw chloropentafluoroethane (CFC-115).